



TRUST LEEBOY.
AS DEPENDABLE AS YOUR DAY IS LONG.

ASPHALT PAVERS

1000



49hp / 11,000 lbs.
Width Up To 13'

5300



64hp / 12,700 lbs.
Width Up To 7'

6150



74hp / 17,550 lbs.
Width Up To 15'

*LBP 150D

7000



64hp / 13,000 lbs.
Width Up To 13'

8500



71hp / 18,100 lbs.
Width Up To 15'

8510



74hp / 17,720 lbs.
Width Up To 15'

8515



74hp / 17,600 lbs.
Width Up To 15'

8520



125 hp / 21,400 lbs.
Width Up To 15'

8530



125hp / 22,520 lbs.
Width Up To 15' 6"

8608



125hp / 21,920 lbs.
Width Up To 15'

8616



127hp / 23,450 lbs.
Width Up To 15' 6"



ASPHALT DISTRIBUTORS

Max 2



12' Full Circulating Folding Spraybar
1,050 to 5,270 Gallons
Plus+1 CAN Bus

Max 3



16' Full Circulating, Extendible Spraybar
1,050 to 5,270 Gallons
Plus+1 CAN Bus, Hot Oil Heat Option

Max 4



24' Full Circulating, Extendible Spraybar
2,050 to 5,270 Gallons
Plus+1 CAN Bus, Hot Oil Heat Option

BROOMS

NV55



Front-Mount Brush
74hp / 6,900 lbs

*LBP FB55

RB50



Center-Mount Brush
74hp / 5,510 lbs

*LBP CB95

NB25



Center-Mount Brush
25hp / 3,050 lbs

ROAD WIDENER

4130



130hp / 27,280 lbs
Wheelbase: 9' 9"

*LBP RW85

FORCE FEED LOADER

3000



L: 34', W" 8'6"
130hp / 20,140 lbs

PATCHER

RA-400



1 Person Operation
VORTEC System • Plus+1 Controls

TACK TANKS

L150



150 Gallons / 1,725 lbs
Engine: Gas or Diesel Available

L300



300 Gallons / 1,950 lbs
Engine: Gas or Diesel Available

L600



600 Gallons / 3,380 lbs
Engine: Gas or Diesel Available

CHIP SPREADER

CSV



275hp/ 23,720 lbs
Spread Width: 8' to 16'

MOTOR GRADERS

685



LeeBoy Controls
L: 22'3", W: 7'8", H:10'2"
130hp / 16,000 lbs.

695



Standard Controls
L: 22'3", W: 7'8", H:10'2"
130hp / 16,000 lbs.

*LBP G700B



ST Engineering LeeBoy, Inc. ■ 500 Lincoln County Parkway Extension ■ Lincolnton, NC 28092 ■ 704.966.3300
For additional products or information, visit our website: www.LeeBoy.com LC-2023.02-EN





ASPHALT PAVER COMPARISON

	1000G	7000C	8500E	8510E	8515E	8520C	8530	8608	8616D	6150	5300B
Length	9' 6"	11'	12' 8"	13' 5"	13' 5"	14' 10"	15'	15' 3"	16' 4"	16' 6"	15' 5"
Height	7'	7'	6' 4"	8'	8'	6' 10"	Low:6'8" High:7'9"	6' 10"	Low:6'8" High:7'10"	7' 8"	5' 9"
Weight	11,000 lbs	13,000 lbs	18,100 lbs	17,720 lbs	17,600 lbs	21,400 lbs	22,520 lbs	21,920 lbs	23,450 lbs	17,550 lbs	12,700 lbs
High/Low Deck	Low Deck	Low Deck	Low Deck	Specify With Order	Operator Choice	Operator Choice	Operator Choice	Operator Choice	Operator Choice	Operator Choice	Low Deck
Steel Track	Steel Standard	Steel Standard	Steel Standard	Optional	Optional	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available
Poly Pad Track	Not Available	Not Available	Optional	Poly Pad Standard	Poly Pad Standard	Poly Pad Standard	Poly Pad Standard	Poly Pad Standard	Poly Pad Standard	Rubber Tire	Poly Pad Standard
Rubber Track	Not Available	Not Available	Optional	Optional	Optional	Optional	Optional	Not Available	Not Available	Not Available	Not Available
Undercarriage	Friction Drive	Friction Drive	Crawler Sprocket	Crawler Sprocket	Crawler Sprocket	Crawler Sprocket	Crawler Sprocket	Oscillating Bogie	Oscillating Bogie	Rubber Tire	Oscillating Bogie
Steering	Cable	Cable	Cable	Electronic Plus+1	Electronic Plus+1	Electronic Plus+1	Electronic Plus+1	Electronic Plus+1	Electronic Plus+1	Electronic Plus+1	Electronic Plus+1
Controls	Cable	Cable	Cable	Cable	Electric/Hydraulic	Electric/Hydraulic	Electric/Hydraulic	Electric/Hydraulic	Electric/Hydraulic	Electric/Hydraulic	Electric/Hydraulic
Propane Screed	Standard Variable up to 13' 1,750 lbs	Standard Variable up to 13' 1,775 lbs	Standard Variable up to 15' 2,510 lbs	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available
Electric Screed	Not Available	Not Available	Optional Variable up to 15' 2,810 lbs	Standard Variable up to 15' 2,810 lbs	Standard Variable up to 15' 2,810 lbs	Not Available	Not Available	Not Available	Not Available	Optional Variable up to 15' 2,810 lbs	Not Available
HD Screed	Not Available	Not Available	Not Available	Optional Variable up to 15' 3,230 lbs	Optional Variable up to 15' 3,230 lbs	Standard Variable up to 15' 3,450 lbs	Not Available	Standard Variable up to 15' 3,450 lbs	Not Available	Optional Variable up to 15' 3,230 lbs	Optional Variable up to 7' 1,425 lbs
HD PRO Screed	Not Available	Not Available	Not Available	Not Available	Not Available	Optional Variable up to 15' 6" 4,150 lbs	Standard, Variable up to 15' 6" 4,150 lbs	Optional Variable up to 15' 6" 4,150 lbs	Standard, Variable up to 15' 6" 4,150 lbs	Not Available	Not Available
Hopper Size	5.5 Ton	6 Ton	7.5 Ton	7.5 Ton	7.5 Ton	9 Ton	9 Ton	9 Ton	9 Ton	7 Ton	7 Ton
Asphalt Delivery	Tilt Hopper	Two 36" Conveyors	Two 36" Conveyors	Two 36" Conveyors	Two 36" Conveyors	Two 36" Conveyors	Two 36" Conveyors	Two 20.5" Conveyors	Two 20.5" Conveyors	Two 20.5" Conveyors	One 13" Conveyor
Augers	9"	9"	12"	12"	12"	12"	12"	12"	12"	12"	12"
Engine Size	49 HP	64 HP	71 HP	74 HP	74 HP	125 HP	125 HP	125 HP	127 HP	74 HP	64 HP
Seats	1	1	1 (2nd optional)	2	2	2	2	2	2	2	N/A
Sloping Extensions	Not Available	Not Available	Not Available	Not Available	Optional	Optional	Standard	Optional	Standard	Optional	Not Available
Truck Hitch	Not Available	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Not Available
Sonic Augers	Optional	Optional	Optional	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Grade Control	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Heated End Gates	Not Available	Not Available	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Not Available
Automatic Temp Control (ATC)	Not Available	Not Available	Not Available	Optional	Optional	Optional	Standard	Optional	Standard	Optional	Standard
Berm Attachment	Not Available	Not Available	Not Available	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Not Available

TRACK

LEGEND SCREEDS

OPTIONAL EQUIPMENT

*Published Weights are approximate weight and will vary contingent on options. Please visit LeeBoy.com or visit your local LeeBoy Dealer for more information. LC-2023.02-EN